

Proposed Code Change State Form 41186R

RETURN TO: INDIANA DEPARTMENT OF HOMELAND SECURITY CODE SERVICES SECTION 302 W. Washington Street Room W246 Indianapolis, IN 46204

F	OR OFFICE USE ONLY	
Recei	ived 7/17/09	
Code	50.10.4-09	

INSTRUCTIONS:

Only TYPED copy accepted.

(KEY - Dashed line through material to be deleted, underline material to be added)

Use second sheet for any material requiring more space.

Section number and title R602.10.5.4 Continuously sheathed braced wall lines Proponent Craig Wagner Address 220 W Van Buren St, Columbia City IN 46725 PROPOSED CODE CHANGE (Check One) Chief Building Inspector/ IABO Code Comm. Member Phone 260-248-3111 PROPOSED CODE CHANGE (Check One) Change to read as follows
Proponent Craig Wagner Address 220 W Van Buren St, Columbia City IN 46725 PROPOSED CODE CHANGE (Check One) Change to read as follows R602.10.5.4 Continuously sheathed braced wall lines. Where a Method CS-SFB, continuously-sheathed braced wall line is used in Seismic Design Categories D₀, D₁ and D₂ or regions where the basic wind speed exceeds 100 miles per hour (45 m/s), the braced
Proponent Craig Wagner Address 220 W Van Buren St, Columbia City IN 46725 PROPOSED CODE CHANGE (Check One) Change to read as follows Add to read as follows Delete and substitute as follows Delete without substitution R602.10.5.4 Continuously sheathed braced wall lines. Where a Method CS-SFB, continuously-sheathed braced wall line is used in Seismic Design Categories D ₀ , D ₁ and D ₂ or regions where the basic wind speed exceeds 100 miles per hour (45 m/s), the braced
Craig Wagner Address 220 W Van Buren St, Columbia City IN 46725 Phone PROPOSED CODE CHANGE (Check One) Change to read as follows Add to read as follows Delete and substitute as follows Delete without substitution R602.10.5.4 Continuously sheathed braced wall lines. Where a Method CS-SFB, continuously-sheathed braced wall line is used in Seismic Design Categories D ₀ , D ₁ and D ₂ or regions where the basic wind speed exceeds 100 miles per hour (45 m/s), the braced
Address 220 W Van Buren St, Columbia City IN 46725 PROPOSED CODE CHANGE (Check One) Change to read as follows Add to read as follows Delete and substitute as follows Delete without substitution R602.10.5.4 Continuously sheathed braced wall lines. Where a Method CS-SFB, continuously-sheathed braced wall line is used in Seismic Design Categories D ₀ , D ₁ and D ₂ or regions where the basic wind speed exceeds 100 miles per hour (45 m/s), the braced
220 W Van Buren St, Columbia City IN 46725 PROPOSED CODE CHANGE (Check One) ☐ Change to read as follows ☐ Add to read as follows ☐ Delete and substitute as follows ☐ Delete without substitution ☐ R602.10.5.4 Continuously sheathed braced wall lines. Where a Method CS-SFB, continuously-sheathed braced wall line is used in Seismic Design Categories D₀, D₁ and D₂ or regions where the basic wind speed exceeds 100 miles per hour (45 m/s), the braced
PROPOSED CODE CHANGE (Check One) Change to read as follows Add to read as follows Delete and substitute as follows Delete without substitution R602.10.5.4 Continuously sheathed braced wall lines. Where a, Method CS-SFB, continuously-sheathed braced wall line is used in Seismic Design Categories D ₀ , D ₁ and D ₂ or regions where the basic wind speed exceeds 100 miles per hour (45 m/s), the braced
EX Change to read as follows ☐ Add to read as follows ☐ Delete and substitute as follows ☐ Delete without substitution R602.10.5.4 Continuously sheathed braced wall lines. Where a, Method CS-SFB, continuously-sheathed braced wall line is used in Seismic Design Categories D₀, D₁ and D₂ or regions where the basic wind speed exceeds 100 miles per hour (45 m/s), the braced
R602.10.5.4 Continuously sheathed braced wall lines. Where a, Method CS-SFB, continuously-sheathed <i>braced wall line</i> is used in Seismic Design Categories D ₀ , D ₁ and D ₂ or regions where the basic wind speed exceeds 100 miles per hour (45 m/s), the <i>braced</i>
provisions of the <i>International Building Code Indiana Building Code</i> . Also, all other exterior <i>braced wall lines</i> in the same <i>story</i> shall be continuously sheathed.
DE ACON AND FIGURE HADAGE
REASON AND FISCAL IMPACT
Method CS-SFB is added to the first line to ensure that other methods of wall bracing are not incorrectly applied to this section. The reference to the IBC is changed to the InBC.
l —
Fiscal impact: there is no increase to the cost of construction.
Fiscal impact: there is no increase to the cost of construction. REVIEW RECOMMENDATION
•
REVIEW RECOMMENDATION
REVIEW RECOMMENDATION Approve